

CT1RD

230 Vac CONTROL UNIT



CODE	DESCRIPTION
CT1RD	For one motor for rolling shutter or sliding gate, 230 Vac, with electric clutch and receiver. In box (1 pc)

TECHNICAL DATA		CT1RD
ELECTRICAL DATA		
input power	Vac/Hz	230/50
output power accessories	Vac (Vdc)	24
max motor power	W	600
max working time	sec	180
max pause time	sec	120
obstacle detection		-
GENERIC DATA		
protection degree	IP	54
dimensions (L - P - H)	mm	160 - 90 - 200
operating temperature	°C	-20 + 55

PLUS

Easy programming with trimmers and dip-switches

Versatile

On board radio receiver

Extractable radio memory

Electric limit switches

OPEN and STOP outputs

Man present functions

Pedestrian open functions

Flashing light output

Electric adjustment of power

ACCESSORIES



RX4X
4 channels plug-in receiver

PC 1



RXM23X
Universal receiver 2 channels, fix o rolling code

PC 1



BOXKEY
Plastic box for two motors control unit


PC 1



BOXKEYS
Plastic box for one motor control unit


PC 1

24 Vdc ACCESSORIES



KBP
Battery back-up kit for 14A control unit

PC 1



KITFIXBATT
Kit fixing batteries 24 Vdc (for BOXKEY)

PCS 2