


AT PLUS OPERATOR 230V - 380V

-  **VOLTAGE 230V - 380V**
-  **RESIDENTIAL**
-  **COLLECTIVE**
-  **GATES UP TO 2500KG**
-  **IN OIL BATH**

 **COLLECTIVE**

Available in ESPRESSO version Page. 47



TECHNICAL FEATURES

	AT PLUS 2500	AT PLUS 2500 TRIPHASE
POWER SUPPLY	230VAC	380VAC
LEAF WEIGHT	2500 KG	2500 KG
PINION	M4-Z16	M4-Z16
ENGINE RPM	1400 RPM	1400 RPM
AVERAGE ABSORPTION	2.4 A	2.4 A
ABSORBED POWER	650 W	950 W
CONDENSER	12.5 UF	-
MOTOR WEIGHT	18 KG	18 KG
NOISE LEVEL	< 30 DBA	< 30 DBA
ENVIRONMENTAL CONDITIONS	-20 / +55° C	-20 / +55° C
PROTECTION DEGREE	IP44	IP44

FEATURES

- Structure in die-cast aluminum, powder painted
- Steel and cast gears obtained from solid
- Stator and mechanical parts in oil bath
- Available with or without control board
- Control unit with built-in receiver and antenna, control board box with air-stop seal against moisture and insects
- Pre-wiring and easy programming software
- High Performance electric motor
- Mechanical limit switch
- Manual lever release with custom key
- Electronic torque control
- Very quiet operation
- Electronic clutch
- Anti-squashing system * (EN 12453)
- Slowing down function * (EN 12453)
- Power supply 230V - 380V

PERFORMANCE REQUIREMENTS

- Operating Cycle Intensive 230V, intensive 380V
- Use frequency 90% (230V) - 90% (380V)
- Speed 9.6 MT/MIN (230V) - 9.6 MT/MIN (380V)

GEARED MOTORS AND ACCESSORIES

CODE	MOD	DESCRIPTION
A3500	AT PLUS 230V	Operator - Up to 2500 kg - Fixing plate - Without control board
A3500/1	AT PLUS TRIPHASE 380V	Operator - Up to 2500 kg - Three-phase 380V - Fixing plate - Without control board
10035/1	AT PLUS 230V C0	Operator - Up to 2500 kg - Fixing plate - Control board and built-in receiver 433 mHz
RVS	RVS	Mechanical slowdown system for gates installed on slopes

 **PZ PALLET**
800x1200xH1300mm 39pcs. 650KG

- For better radio reception, the use of an external antenna CODE. is recommended.
230/1
- In cold temperatures, the performance of the actuator can be significantly reduced

KIT CONTENT

THE KIT CONTAINS 1 SWITCHGEAR + ACCESSORIES

 **PZ PALLET**
800x1200x1000mm | 25 pcs. 450KG



CODE. E102
Control board 230V



CODE. E107
Control board 380V



CODE. 12/C
Pair of photocells



CODE. 23/8
LED flashing light



CODE. 198/5
Key selector



CODE. E010
Remote control



CODE. 1658
Warning sign

EXTRA ACCESSORIES



CODE. RVS
Mechanical slowdown system for gates installed on slopes

* Functions guaranteed with VDS electronics